

IB1006	
Inductive proximity sensor	
Metal thread M12 x 1.0	
Cable	
Size 55mm	
Sensing range 4mm[f]	
Non-Flush	

Electric design	DC 3 Wire
Output	PNP NC
Operating voltage [V]	10...36 DC
Current loading [mA]	100
Short-circuit protection	Yes
Reverse polarity protection	Yes
Overload protection	Yes
Voltage drop [V]	<2.5
Consumed current[mA]	<15
Real sensing range [mm]	4±10%
Operating range [mm]	0...3.2
Switch-point drift [%/Sr]	-10...10
Hysteresis [%/Sr]	3...20
Switching frequency [Hz]	700
Adjustment factors	Low carbon steel=1 /Stainless steel approx 0.7 /Brass approx 0.5 / Alumium approx 0.4 / Copper approx 0.3
Operating temperature [°C]	-25...75
Ambient humidity	35...95
Protection classification	IP67

Dimension	
-----------	--

Housing material	Stainless steel , Sensing face: PBT
Switching state display LED	Red (90°)
Connection	PVC-Cable /2m;3x0.14mm ²
Wiring	
Core color	
BN +	
BU -	
BK Signal Line	

Accessory(Included)	Two fixed nuts
---------------------	----------------