





<p>IC1205 Inductive proximity sensor Metal thread M18 x 1.0 High temperature Cable Size 53mm Sensing range 8mm[nf] Non-Flush</p>	
Electric design	DC PNP
Output	NO 
Operating voltage [V]	10...36 DC
Current loading [mA]	250
Short-circuit protection	Yes
Reverse polarity protection	Yes
Overload protection	Yes
Voltage drop [V]	<2.5
Consumed current[mA]	<15(24VDC)
Real sensing range [mm]	8 ± 10%
Operating range [mm]	0...6.4
Switch-point drift[%/Sr]	-10...10
Hysteresis[%/Sr]	1...15
Switching frequency[Hz]	400
ESD[KV]	6KV III
EFT[KV]	2KV III
Walkie talkie experiment[mm]	<1
Adjustment factors	Low carbon steel=1 /Stainless steel approx 0.7 /Brass approx 0.4 / Aluminum approx 0.3 / Copper approx 0.2
Operating temperature[°C/°F]	-25°C...120°C/-13°F...248°F
Protection classification	IP67
Dimension[mm]	
Housing material	不锈钢304 ; 感应面: PBT+GF
Switching state display LED	Red(90°)
Connection	硅胶Cable /2m; 3x0.34mm2
Wiring Core color  BN + BU - BK Signal Line	
Accessory(Included)	Two fixed nuts