







<p>CB0017 Capacitive Proximity Sensor Plastic housing M30mm X1.5mm M12 Socket Against electromagnetic interference Sensing range 15mm[nf] Adjustable 3...15mm Non-flush</p>	 <p>CE RoHS</p>
<p>Electric design</p>	<p>DC PNP</p>
<p>Output</p>	<p>NO  NC </p>
<p>Operating voltage[V]</p>	<p>10...36 DC</p>
<p>Current loading[mA]</p>	<p>250</p>
<p>Short-circuit protection</p>	<p>Yes</p>
<p>Reverse polarity protection</p>	<p>Yes</p>
<p>Overload protection</p>	<p>Yes</p>
<p>Voltage drop[V]</p>	<p>< 2.5</p>
<p>consumed current[mA]</p>	<p>< 13 (24V)</p>
<p>Real sensing range[mm]</p>	<p>15 ± 10%</p>
<p>Operating range[mm]</p>	<p>0...12.1</p>
<p>Switch-point drift [%/Sr]</p>	<p>-15...15</p>
<p>Hysteresis[%/Sr]</p>	<p>1...15</p>
<p>Switching frequency [Hz]</p>	<p>40</p>
<p>Adjustment factors</p>	<p>Water=1 / Glass approx.0.4 / Ceramic approx .0.2 / PVC approx.0.2</p>
<p>Operating temperature [°C]</p>	<p>-25°C...80°C</p>
<p>Protection classification</p>	<p>IP67</p>
<p>Dimension</p>	
<p>Housing material</p>	<p>PBT+GF</p>
<p>Switching state display LED</p>	<p>Red</p>
<p>Connection</p>	<p>M12 Socket</p>
<p>Wiring Core color</p> 	
<p>Accessory (Included)</p>	<p>Fixed nut and screwdriver</p>